

## Door Signage Display





**TPC-310 AND** 

Using CUREVISION digital door signage, the relevant information is displayed directly from your EHR system, ensuring accurate information is displayed at all times. CureVision digital door signage is beneficial for reducing perceived wait times in waiting areas like emergency rooms and outpatient procedural departments. For example, you can display wait times in emergency rooms by using CUREVISION digital signage.

Make your message concise and visually appealing to increase patient, guest, and visitor satisfaction. Promote other services within the hospital or at other locations through cross-promotion. Provide an update on future expansion and other upcoming services that are going to be added. Provide patients with an introduction to new physicians and staff members.

## **Features**

- Customizable Color and Design
- Industrial Components for Continuous Operation
- 0-60 ° C Working Temperature
- Instant Connection Analysis and Solution Support Via Remote Connection





			-	2 C	-		
u	ĸ	u	ER	" "	·u	u	

CPU	: All Winner R18, Quad Core,Cortex A53 1.5 GHz
Feed	: 110/220V AC, 12/24V DC, POE
RAM	: 2GB
HDD	: EMMC8G / EMMC32G (Optional)
Wi-Fi	: 802.11 b / g (Optional)
SYSTEM	
CPU	: All Winner R18, Quad Core,Cortex A53 1.5 GHz
Cache	: By CPU
Memory	: 1G LPDDR3 (Option 2G)
Video RAM	: By CPU
Chipset	: By CPU
Watchdog Timer	: Support
System	: Android 6.0
INPUT/OUTPUT	
Serial Port	: 3 x RS-232 ports (Optional)
USB Port	: 2 x USB 2.0
LAN	: 1 x LAN Realtek Gigabit Ethernet
Wireless LAN	: 802.11 b / g (Optional)
Audio	: Support L/R Phone Jack and 10W / 8Rx2

## **DATA STORAGE**

HDD Type	: Vibration Resistant					
HDD Storage	: EMMC8G / EMMC32G (Optional)					
FEED						
Input	: 110/220V AC, 12/24V DC, POE					
Adapter	: Adapter Included					
LCD SCREEN						
Size / Type	: 10.1" / 16:9					
Max. Resolution	: 1280 x 800					
Pixel Pitch	: 0.297mm x 0.297mm					
Max. Color	: 16.7 M					
Brightness	: 250cd					
Contrast Ratio	: 700/1					
Viewing Angle	: 160°(H),160°(V)					
Back Light MTBF	: 50,000 Hours					
Touch Screen	: 10.1" Capacitive Touch					
VIDEO OUTPUT						
Туре	: HDMI					
Max Resolution	: 1920x1080 @ 60Hz					
ENVIRONMENTAL FEATURES						
Working Temp	: 0~60°C					
Storage Humidity	: 5~95% (non-condensing)					
Case	: Heavy Duty Metal Case					
Front Frame	: Stainless Steel					
Weight	: Variable According to Monitor Size					
Dimensions	: Variable According to Monitor Size					
Mounting	: Wall					



