

CUREVISION Tele-Visit Solution has been developed to make contactless visits in intensive care units. Inpatients' relatives can visit their relatives with CureVision Tele-Visit and obtain information from doctors. The video call feature allows doctors to monitor patient's conditions and consult remotely.

CUREVISION Tele-Visit Video Call Platform does not capture or store personal information about its users, such as their name, phone number, or e-mail address. Therefore, CUREVISION Tele-Visit Solution can also be applied to clinical assistant applications.

Features

- Computer with Electromagnetic and Safety Compatibility Required for Medical Standards and Intensive-Care Conditions
- An Antibacterial Device Suitable for General Hospital and Intensive-Care Hygiene
- Mouse and Keyboard with Antibacterial Properties
- A 21-inch Touchscreen with High Resolution
- High-Quality Images and Sound for a Smooth Conversation
- In the Same Session, Up to 6 People Can Participate in Video Calls
- Data Communication Via Wireless Technology
- Easy-to-Use Application Interface



Tele-Visit System



SYSTEM

CPU	: Intel® N4200 / i3 / i5 / i7
Cache	: By CPU
Memory	: 2 x DDR3 SO-DIMM Sockets, Max. Capacity 32 GB
Video RAM	: Intel® HD Graphics
Chipset	: By CPU
Watchdog Time	r: 255 Level Reset
INPUT/OUTPUT	
Serial Port	: RS-232/422/485
Parallel Port	: N.A.
USB Port	: 4 x USB 3.0
LAN	: Dual Lan; Dual Gigabit Ethernet 10/100/1000
Wireless LAN	: 802 11bg / n (Optional)
Audio	: Line In & Out (AC'97 Codec Audio)

DATA STORAGE

HDD Type	: 2.5 " HDD in a Vibration Resistant Bay
SSD	: 64 GB / 128 GB / 256 GB
FEED	
Input	: 110 / 220VAC or / 24VDC
LCD SCREEN	
Size / Type	: 21.5 "LVDS (16: 9 Widescreen)
Max. Resolution	: 1920 x 1080, Fu ll HD
Pixel Pitch	: 0 297mm x 0 297mm
Max. Color	: 16.7 M
Brightness	: 350cd
Contrast Ratio	: 1000/1
Viewing Angle	: 160°(H),160°(V)
Back Light MTBF	: 50,000 Hours
Touch Screen	: 21,5" Touch - Projected Capacitive
MECHANICAL & ENVIRONMENTAL FEATURES	
Operating Temp	: 0~60℃
Storage Humidity	: 5~95% (non-condensing)
Front Frame	: IP65 Front Panel Protection
EXTRA VIDEO OUTPUT	
Туре	: HDMI/VGA
Max. Resolution	: 4096x2160

